(19) World Intellectual Property Organization International Bureau



(43) International Publication Date 29 December 2004 (29.12.2004)

PCT

$\begin{array}{c} \hbox{\scriptsize (10) International Publication Number} \\ \hbox{\scriptsize WO 2004/114005} \quad A1 \end{array}$

(51) International Patent Classification⁷: G02F 1/1337, C09K 19/02

(21) International Application Number:

PCT/SE2004/000880

(22) International Filing Date: 7 June 2004 (07.06.2004)

(25) Filing Language:

English

(26) Publication Language:

English

 (30)
 Priority Data:
 23 June 2003 (23.06.2003)
 SE

 0301810-8
 23 June 2003 (23.06.2003)
 SE

 0303041-8
 18 November 2003 (18.11.2003)
 SE

 SE2004/000300
 4 March 2004 (04.03.2004)
 SE

(71) Applicant (for all designated States except US): ECSI-BEO AB; Hugo Grauers gata 3, S-412 96 Göteborg (SE).


(72) Inventors; and

(75) Inventors/Applicants (for US only): KOMITOV, Lachezar [SE/SE]; Landalabergen 26, S-411 29 Göteborg (SE). HELGEE, Bertil [SE/SE]; Fullriggaregatan 23, S-426 74 Västra Frölunda (SE). FELIX, Johan [SE/SE]; Hantverkaregatan 1, S-411 29 Göteborg (SE).

- (74) Agent: AWAPATENT AB; P.O. Box 11394, S-404 28 Stockholm (SE).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,

[Continued on next page]

(54) Title: A LIQUID CRYSTAL DEVICE AND A METHOD FOR MANUFACTURING THEREOF



(57) Abstract: The invention relates to a liquid crystal device comprising a liquid crystal bulk layer and a surface-director alignment layer comprising side-chains arranged to interact with the bulk layer, wherein the orientation of the bulk layer molecules and the orientation of said side-chains each is directly controllable by an electric field via dielectric coupling, thus resulting in a decreased total time period (rise and decay times) needed to switch and relax the liquid crystal bulk molecules in response to an applied external field. The invention also relates to a method for manufacturing a liquid crystal device and a method of controlling a liquid crystal bulk layer.

04/114005 A1



SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

— as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, NA,

SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

— of inventorship (Rule 4.17(iv)) for US only

Published:

- with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

10

30

A LIQUID CRYSTAL DEVICE AND A METHOD FOR MANUFACTURING THEREOF

Technical field

The present invention generally relates to the field of liquid crystals. More specifically, the present invention relates to a liquid crystal device comprising a liquid crystal bulk layer presenting a surface-director at a bulk surface thereof, and a surface-director alignment layer arranged to interact with the bulk layer at said bulk surface for facilitating the obtaining of a preferred orientation of the surface-director of the bulk layer.

The invention also relates to a method for manufacturing a liquid crystal device and a method of controlling a liquid crystal bulk layer.

Technical background

- Liquid crystals, widely used at present as electrooptical media in display devices, are organic materials
 with anisotropic physical properties. Liquid crystal
 molecules are generally long rod-like molecules, socalled calamitic molecules, which have the ability to

 20 align along their long axis in a certain preferred direction (orientation). The average direction of the molecules is specified by a vector quantity and is called director.
- It may be noted, however, that there also exist liq-25 uid crystal molecules that are disc-like, so-called discotic molecules.

The operation of the liquid crystal displays is based on the changes of the optical characteristics, such as light transparency, light absorption at different wavelengths, light scattering, birefringence, optical activity, circular dichroism, etc, of the liquid crystal in the display caused by an applied electric field (direct coupling).

WO 2004/114005 PCT/SE2004/000880

2

One of the basic operational principle of liquid crystal displays and devices is the switching of the orientation of the liquid crystal molecules by an applied electric field that couples to the dielectric anisotropy of the liquid crystal (dielectric coupling). Such a coupling gives rise to an electro-optic response quadratic with the applied electric field, i.e. independent of the field polarity. There exist a number of different types of LCDs (liquid crystal displays) whose operation is based on dielectric coupling, especially dynamic scattering displays, displays using deformation of homeotropically aligned nematic liquid crystal, Schadt-Helfrich twisted nematic (TN) displays, super twisted nematic (STN) displays, in-plane switching (IPS) nematic displays.

10

15

25

30

For modern applications, a LCD should possess several important characteristics, such as a high contrast and brightness, a low power consumption, a low working voltage, short rise (switching) and decay (relaxation) times, a low viewing angle dependence of the contrast, a grey scale or bistability, etc. The LCD should be cheap, easy to produce and to work with. None of the prior-art LCDs is optimised concerning all the important characteristics.

A nematic liquid crystal material exhibits the simplest liquid crystalline structure, i.e. an anisotropic liquid. In a nematic material, the liquid crystal molecules are aligned toward a particular direction in space, but the centre of mass of molecules is not ordered.

In most of the conventional nematic liquid crystal displays, operating on the basis of the dielectric coupling, the electric field is applied normally to the liquid crystal bulk layer (i.e. normally to the confining substrates) and the liquid crystal bulk molecules are switched by the electric field in a plane perpendicular to the confining substrate surfaces (so-called out-of-plane switching). These displays are usually slow, and

WO 2004/114005 PCT/SE2004/000880

3

nearly all suffer from non-satisfactory angular dependence of the contrast.

There is also another type of LCDs with in-plane switching, in which the electric field is applied along the liquid crystal bulk layer (i.e. in parallel with the confining substrates) and the liquid crystal bulk molecules are switched in a plane in parallel with the confining substrate surfaces. These displays exhibit a very small angular dependence of the image contrast but the resolution and the switching time are not satisfactory.

10

15

20

25

30

35

In the liquid crystal displays discussed above, the desired initial alignment of the liquid crystal layer in the absence of an external field, such as an electric field, is generally achieved by appropriate surface treatment of the confining solid substrate surfaces, such as by applying a so-called (surface-director) alignment layer (also called orientation layer) on the confining substrate surfaces facing said liquid crystal bulk. The initial liquid crystal alignment is defined by solid surface/liquid crystal interactions. The orientation of the liquid crystal molecules adjacent the confining surface is transferred to the liquid crystal molecules in the bulk via elastic forces, thus imposing essentially the same alignment to all liquid crystal bulk molecules.

The director of the liquid crystal molecules near the confining substrate surfaces (herein also called surface-director) is constrained to point in a certain direction, such as perpendicular to (also referred to as homeotropic or vertical) or in parallel with (also referred to as planar) the confining substrate surfaces. The type of alignment in liquid crystal displays operating on the coupling between liquid crystal dielectric anisotropy and applied electric field is chosen in accordance with the sign of the dielectric anisotropy, the direction of the applied electric field and the desired type of switching mode (in-plane or out-of plane).

10

15

20

25

35

In out-of-plane switching liquid crystal cells employing a liquid crystal bulk having a negative dielectric anisotropy, it is important to uniformly orient the director of the liquid crystal bulk molecules (in the field-off state) vertically to the substrate surfaces (so-called homeotropic alignment).

An example of a method for establishing a homeotropic alignment comprises coating the confining substrate surfaces with a surfactant, such as lecithin or hexadecyltrimethyl ammonium bromide. The coated substrate surfaces is then also preferably rubbed in a predetermined direction, so that the field-induced planar alignment of the liquid crystal molecules will be oriented in the predetermined rubbing direction. This method may give good results in laboratory studies, but has never found industrial acceptance due to that long term stability is not obtained as the alignment layer is slowly dissolved in the bulk liquid crystal (J. Cognard, Mol. Cryst. Liq. Cryst., Suppl. Ser., 1982, 1, 1).

In out-of-plane switching liquid crystal cells employing a liquid crystal bulk having a positive dielectric anisotropy, it is important to uniformly orient the director of the liquid crystal bulk molecules (in the field-off state) in parallel with the substrate surfaces (so-called planar alignment). For twisted nematic liquid crystal cells, it is also important to orient the liquid crystal bulk molecules at a certain inclined orientation angle (pre-tilt angle) to the substrate.

Known methods for establishing planar alignment is, 30 for instance, the inorganic film vapour deposition method and the organic film rubbing method.

In the inorganic film vapour deposition method, an inorganic film is formed on a substrate surface by vapour-deposition of an inorganic substance, such as silicon oxide, obliquely to the confining substrate so that the liquid crystal molecules are oriented by the inorganic film in a certain direction depending on the inor-

10

15

20

25

30

35

ganic material and evaporation conditions. Since the production cost is high, and the method thus is not suitable for large-scale production, this method is practically not used. According to the organic film rubbing method, an organic coating of, for instance, polyvinyl alcohol, polyoxyethylene, polyamide or polyimide, is formed on a substrate surface. The organic coating is thereafter rubbed in a predetermined direction using a cloth of e.g. cotton, nylon or polyester, so that the liquid crystal molecules in contact with the layer will be oriented in the rubbing direction.

Polyvinyl alcohols (PVA) are commercially rarely used as alignment layers since these polymers are hydrophilic, hygroscopic polymers that may adsorb moisture adversely affecting the molecular orientation of the polymer and thus the liquid crystal device performance. In addition, PVA may attract ions which also impairs the liquid crystal device performance.

Also polyoxyethylenes may attract ions, thus resulting in impaired liquid crystal device performance.

Polyamides have a low solubility in most commonly accepted solvents. Therefore, polyamides are seldom used commercially in liquid crystal device manufacturing.

Polyimides are in most cases used as organic surface coating due to their comparatively advantageous characteristics, such as chemical stability, thermal stability, etc.

In in-plane switching liquid crystal cells employing a liquid crystal bulk having a positive or negative dielectric anisotropy, it is important to uniformly orient the director of the liquid crystal bulk molecules in parallel with the substrate surfaces. The aligning methods used in this case are similar to those used for out-of-plane switching of liquid crystal cells employing a liquid crystal bulk having a positive dielectric anisotropy.

In in-plane switching liquid crystal cells employing a liquid crystal bulk having a positive dielectric ani-

PCL XL error

Subsystem: IMAGE

Error:

ExtraData

Operator:

ReadImage

Position:

4331

APPLICATION NO. (If known,	100 37 CFR 1.5) INTERNA	TIONAL APPLICATION N	• .	EYS DOCKET NUM	
Unassigned CO CT/SE2004/000880 ATTORN Unassigned CO CT/SE2004/000880				003301-249 CALCULATIONS PTO USE ONLY	
' institute institute the following assignment				CALCULATIONS	PIOUSE CITET
R Applicant(s) requests that the published application include the locating design.					
Information:ECSIBEO PPF2 AB, Go					
E-VAIRAR II LA					1
				ļ	
				•	
The following fees are s	ubmitted:			\$ 300.00	
Basic Filing Fee (1631)				\$ 300.00	
Surcharge of \$130.00 (161)	7) for furnishing the oath	or declaration later than	20 🔲 30		
months from the earliest cla	med priority date (37 C	NUMBER EXTRA	RATE	\$	
CLAIMS	NUMBER FILED		× \$50.00 (1615)	\$ 0.00	
Total Claims	20 -20	 	× \$200.00 (1614)	 	
Independent Claims	3 -3	= 0			
MULTIPLE DEPENDENT CLAIM(S) (if applicable) + \$360.00 (1616 + \$200.00 (1633					
Examination Fee					
Search Fee + \$500.00 (1632)				\$ 500.00	
App. Size Fee (add \$250.00 for each add 150 sheets exceeding 100 sheets)				\$ 1,000.00	
TOTAL OF ABOVE CALCULATIONS				\$ 1,000.00	
Applicant claims small entity status. See 37 CFR 1.27. The fees indicated above				\$ 500.00	
are reduced by 1/2.				\$ 500.00	
Processing fee of \$130.00 (1618) for furnishing the English translation later than 20 30				\$ 0.00	
months from the earliest claimed priority date (37 CFR 1.492(f)).				\$0.00	
TOTAL NATIONAL FEE:				= \$ 500.00	
Fee for recording the enclosed assignment (37 CFR 1.21(h)). The assignment must be				\$ 40.00	
accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31). \$40.00 (8021) per property +				\$ 540.00	· ·
		TOTAL	L FEES ENCLUSED	Amount to be	
		•	•	refunded :	2
a. X A check in the amount of \$540.00 to cover the above fees is enclosed.				charged	:
A check in the amount of				to cover the abo	ove fees. A
 b. Please charge my duplicate copy of the co	.				
=	. is basely outbooked t	o charge any additional fe	es which may be rec	uired, or credit any	overpayment to
C. IXI The Commissione Deposit Account I	No. <u>02-4800</u> . A d	uplicate copy of this sheet	is enclosed.		
d. Charge		Form PTO-2038 is attac			
NOTE: Where an appro				petition to revive (3	7 CFR 1.137(a)
NOTE: Where an appro or (b)) must be filed and	priate time limit under granted to restore the	application to pending	status.		
			4	_	
			\mathcal{A}		411
SEND ALL CORRESPON	NDENCE TO:		(),1	n B. L Julke	ah.
Buchanan Ingersoll PC					-/
Including attorneys from Burns, Doane, Swecker & Matris					
P.O. Box 1404				Benton S. Duffe	ett, Jr
Alexandria, Virginia 22313-1404					
(703) 836-6620					
				30 <u>23, E</u>	ecember 2005
1			REGISTRAT	ION NO.	DATE